



Narrow Double Sided (NDS)

Feste Räder (SW)
 Pulverbeschichtung.
 Sicherheitsleiste.
 Zaubernden Räder.

Pneumatische Räder (PW)
 Sicherheitsgurt.
 E.P.D.M Gummi.



IMPERIAL UNITS

NDS-1200-SW

W 28 5/8 x L 46 7/16 x H 42 15/16
 LW 5 3/4 x LH 31 1/2
 Arbeitsbelastung 1100 lbs

NDS-1200-PW

W 31 1/16 x L 46 7/16 x H 45 9/16
 LW 5 3/4 x LH 31 1/2
 Arbeitsbelastung 1100 lbs

NDS-1500-SW

W 28 5/8 x L 58 1/4 x H 42 15/16
 LW 5 3/4 x LH 31 1/2
 Arbeitsbelastung 1100 lbs

NDS-1500-PW

W 31 1/16 x L 58 1/4 x H 45 9/16
 LW 5 3/4 x LH 31 1/2
 Arbeitsbelastung 1100 lbs

METRIC SYSTEM

NDS-1200-SW

W 711 x L 1180 x H 1090
 LW 146 x LH 800
 Arbeitsbelastung 500 kgs

NDS-1200-PW

W 789 x L 1180 x H 1157
 LW 146 x LH 800
 Arbeitsbelastung 500 kgs

NDS-1500-SW

W 711 x L 1480 x H 1090
 LW 146 x LH 800
 Arbeitsbelastung 500 kgs

NDS-1500-PW

W 789 x L 1480 x H 1157
 LW 146 x LH 800
 Arbeitsbelastung 500 kgs